



7284 South HWY 81 - PO Box 813
HENNESSEY, OK 73742

Office: (405) 853-2223

Cell: (405) 853-1519

Fax: (405) 853-2470 quickpump@pldi.net

Product Information Sheet

QPS-106

Paraffin Treating Compound

| | | | |
|------------------------|--------------------|-----------------------|---------|
| Appearance: | Light amber liquid | Density: | 8.1 lbs |
| Odor: | Aromatic | Spec. Gravity: | 0.98 |
| Freezing point: | Below -20F | pH: | 6-7 |
| Flash point: | 120F | Solubility: | Oil |

Quick Pump Service QPS-106 is a specific blend of organic materials designed to both prevent paraffin deposition and dissolve existing paraffin. QPS-106 is highly effective in preventing paraffin deposition in tubing, production lines and treating vessels. QPS-106 Good for hot oil Production tanks with heavy bottoms or hot oil down Tbg.QPS-106 will dissolve solidified paraffin in production systems. It has emulsifying properties to prevent wax emulsions in the interface. QPS-106 is a highly active paraffin compound designed for extreme paraffin problems.

QPS-106 treating rates will vary with the type of crude, temperature and exposure time. Batch treating with 5-55 gallons down the backside and circulating for 8-12 hours, will normally provide excellent cleaning of the system. Continuous injection of 500-1000 PPM for 2-5 days to clean the system, then a reduction to 150-500 PPM; will provide a solution for paraffin control. Tank bottoms can be cleaned by batching 5-15 gallons and circulating back through the surface vessels.

QPS-106 is a flammable liquid! Do not handle or use this product near heat, sparks or open flames. Wear rubber gloves and goggles when handling this product. Avoid contact with body and prolonged breathing of vapor. For further information regarding this product refer to the SDS sheet.

For pricing and specific information regarding QPS-106, please contact your Quick Pump Service. Sales professional.

QPS-106 is available in 55 gallon non-returnable drums or in bulk

