

Quick Chemicals LLC



**P.O. Box 813
Hennessey OK 73742
(405)853-1519**

Product Information Sheet

PS-106

Paraffin Treating Compound

Appearance:	Light amber liquid	Density:	8.1 lbs
Odor:	Aromatic	Spec. Gravity:	0.98
Freezing point:	Below -20F	pH:	6-7
Flash point:	120F	Solubility:	Oil

Quick Chemicals PS-106 is a specific blend of organic materials designed to both prevent paraffin deposition and dissolve existing paraffin. PS-106 is highly effective in preventing paraffin deposition in tubing, production lines and treating vessels. P-106 Good for hot oil Production tanks with heavy bottoms or hot oil down Tbg.PS-106 will dissolve solidified paraffin in production systems. It has emulsifying properties to prevent wax emulsions in the interface. PS-106 is a highly active paraffin compound designed for extreme paraffin problems.

PS-106 treating rates will vary with the type of crude, temperature and exposure time. Batch treating with 5-55 gallons down the backside and circulating for 8-12 hours, will normally provide excellent cleaning of the system. Continuous injection of 500-1000 PPM for 2-5 days to clean the system, then a reduction to 150-500 PPM; will provide a solution for paraffin control. Tank bottoms can be cleaned by batching 5-15 gallons and circulating back through the surface vessels.

PS-106 is a flammable liquid! Do not handle or use this product near heat, sparks or open flames. Wear rubber gloves and goggles when handling this product. Avoid contact with body and prolonged breathing of vapor. For further information regarding this product refer to the MSDS sheet.

For pricing and specific information regarding PS-106, please contact your Quick Chemicals sales professional.

PS-106 is available in 55 gallon non-returnable drums or in bulk